

NOISE-FREE SPROCKET WHEEL

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a sprocket wheel, and more particularly to a noise-free sprocket wheel. The sprocket wheel has a driving ring with multiple through holes defined to respectively receive therein a driving block and an elastic belt mounted on the driving blocks. Each block is so configured that when the sleeve in the sprocket wheel is rotating and the sprocket wheel body is not rotating, the driving blocks are tilted so that there is no connection between the sleeve and the sprocket wheel body. Thus, the sprocket wheel is noise-free in comparison with prior art sprocket wheels.

2. Description of Related Art

With reference to Figs. 6 and 7, when a pedal (50) is turned, a rear wheel (53) is driven to rotate via a conventional sprocket wheel (51) and a chain (52). The conventional sprocket wheel (51) is composed of a sleeve (70) connected to the axle (not shown) of the rear wheel (53) and a sprocket wheel body (60).

The sleeve (70) has at least two recesses (72) defined in an outer periphery thereof and each recess (72) receives therein a clamp (71) and a spring (73) connected to a distal end of the clamp (71). The sprocket wheel body (60) has a first tooth (61) formed on an inner periphery thereof and a second tooth (62) formed on an outer periphery thereof. With such an arrangement, the clamps (71) are able to be detachably connected to the first teeth (61). The chain (52) is mounted on the second teeth (62). When the user turns the pedals (50), the chain (52) will drive the sprocket wheel body (60) to rotate in a clockwise direction (as shown from the drawing). In the meantime, the first teeth (61) on the inner periphery of the sprocket wheel body (60) engage with the clamp (71) such that the sleeve (70) rotates simultaneously with the axle of the rear wheel (53).

1 When the user is not turning the pedals (50) yet the bicycle is still moving
2 forward, such as when going downhill, the sprocket wheel body (60) remains still.
3 However, the sleeve (70) still moves along the rear wheel (53) so that the clamp (71)
4 moves over the first teeth (61) and thus noise is generated. Besides, the angular distance
5 θ between two pitches of two first teeth (61) causes a gap in power transmission. That
6 is, the power transmission from the chain (52) is not able to be transmitted to the
7 sprocket wheel body (60) at the moment when the user turns the pedals (50). Although
8 there are at least two clamps (71), the force from the chain (52) to the sprocket wheel
9 body (60) normally is applied to a single clamp (71). When the force is too large or too
10 sudden, the clamp might easily be broken.

11 To overcome the shortcomings, the present invention intends to provide an
12 improved sprocket wheel to mitigate or obviate the aforementioned problems.

13 SUMMARY OF THE INVENTION

14 The primary objective of the invention is to provide an improved sprocket wheel
15 having multiple driving blocks movably received in the sprocket wheel body so that
16 when the driving blocks are tilted, the rotation of the sleeve is not able to drive the
17 sprocket wheel body to rotate simultaneously. That is, if the sprocket wheel body is still
18 and the sleeve is still rotating, the driving blocks will be tilted so that there is no
19 connection between the sleeve and the sprocket wheel body and thus noise is eliminated.

20 Another objective of the present invention is to provide an elastic belt mounted
21 on each of the driving blocks so as to secure the positions of the driving blocks in the
22 driving ring.

23 Other objects, advantages and novel features of the invention will become more
24 apparent from the following detailed description when taken in conjunction with the
25 accompanying drawings.

1 BRIEF DESCRIPTION OF THE DRAWINGS

2 Fig. 1 is an exploded perspective view of the sprocket wheel of the present
3 invention;

4 Fig. 2 is an exploded view of the sleeve and the assembled sprocket wheel body,
5 the driving ring and the side cap;

6 Fig. 3 is a cross sectional showing the inner structure of the sprocket wheel of
7 the present invention;

8
9 Fig. 4 is an enlarged side view showing the application of the sprocket wheel,
10 wherein the sprocket wheel body is rotating simultaneously with the sleeve;

11 Fig. 5 is an enlarged side view showing the application of the sprocket wheel,
12 wherein the sprocket wheel body remains still while the sleeve is rotating;

13 Fig. 6 is a perspective view of a bicycle with a conventional sprocket wheel; and

14 Fig. 7 is a schematic side view showing the application of the conventional
15 sprocket wheel.

16 DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

17 With reference to Fig. 1, the sprocket wheel of the present invention has a
18 sprocket wheel body (10), a driving ring (20), a sleeve (30) and a side cap (40).

19 The sprocket wheel body (10) is hollow and has teeth (11) formed on an outer
20 periphery of the sprocket wheel body (10) to adapt to a chain of the bicycle (not shown),
21 a space (12) defined in the center of the sprocket wheel body (10), a first annular recess
22 (121) and a second annular recess (122). Both the first and second annular recesses
23 (121,122) are formed on a peripheral edge of the sprocket wheel body (10) and opposite
24 to each other.

25 The driving ring (20) is able to be received in the space (12) of the sprocket

1 wheel body (10) and has an outer skirt (21) with multiple partitions (22) formed in the
2 outer skirt (21) so as to define multiple through holes (23) in the driving ring (20) for
3 receiving therein multiple driving blocks (25). Each driving block (25) is configured to
4 have a length L slightly larger than a length of the through hole (23) and a width W
5 slightly smaller than a width of the through hole (23). The driving block (25) has a
6 cutout (251) defined in a mediate portion thereof and an arcuate top face (252). After
7 each driving block (25) is received in a corresponding one of the through holes (23) and
8 the cutouts (251) are aligned with one another, an elastic belt (24) is provided to be
9 received in the aligned cutouts (251) so as to secure the driving blocks (25) in position.

10 The sleeve (30) has a flange (31) formed on one peripheral edge thereof to
11 correspond to the second annular recess (122), an inner threading (32) and an outer
12 threading (33).

13 The side cap (40) has a ball receiving recess (41) defined to correspond to the
14 first annular recess (121) of the sprocket wheel body (10) for receiving therein multiple
15 balls (42) and an inner threading (43) formed to correspond to the outer threading (33) of
16 the sleeve (30). An annular pad (44) is provided to correspond to one side of the driving
17 ring (20).

18 With reference to Figs. 2, 3 and still taking Fig. 1 for reference, when the
19 sprocket wheel of the present invention is to be assembled, the driving blocks (25) are
20 received in the through holes (23) and then the elastic belt (24) is provided to be received
21 in the aligned cutouts (251) so as to secure the driving blocks (25) in the driving ring
22 (20). Then, the driving ring (20) is received in the space (12) with the annular pad (44)
23 attached to one side of the driving ring (20). Thereafter, the sleeve (30) is inserted into
24 the hollow driving ring (20) which is received in the space (12) to be threadingly
25 connected to the side cap (40).

1 It is to be noted especially in Fig. 3 that after the mating of the ball receiving
2 recess (41) and the first annular recess (121), the balls (42) are securely retained.

3 With reference to Fig. 4, when the chain (not numbered) is driven by the turning
4 of the pedals (not shown nor numbered), due to the secure connection between the chain
5 and the teeth (11), the sprocket wheel body (10) is driven by the chain. The driving
6 blocks (25) are securely engaged with an inner periphery of the sprocket wheel body (10)
7 and an outer periphery of the sleeve (30) such that the rotation of the sprocket wheel
8 body (10) drives the sleeve (30) to rotate simultaneously. Because the inner threading
9 (32) of the sleeve (30) is threadingly connected to the axle (not shown) of the rear wheel
10 of the bicycle, the rear wheel of the bicycle is also driven to rotate.

11 With reference to Fig. 6, if in a situation such as coasting down a hill the chain
12 remains still and the sleeve (30), due to the secure engagement with the rear wheel, will
13 still be rotating. The rotation of the sleeve (30) tilts one end of the driving blocks (25),
14 whereby the top faces (252) of the driving blocks (25) are no longer in contact with the
15 inner periphery of the sprocket wheel body (10) and therefore, the sprocket wheel is
16 substantially silent.

17 However, when the sprocket wheel body (10) is rotated again due to the driving
18 of the chain and the rotation velocity of the sprocket wheel body (10) is larger than a
19 rotation velocity of the sleeve (30), the tilted driving blocks (25) will return to their
20 original position and then securely engage between the inner periphery of the sprocket
21 wheel body (10) and the outer periphery of the sleeve (30) so as to drive the rear wheel to
22 rotate.

23 Even though numerous characteristics and advantages of the present invention
24 have been set forth in the foregoing description, together with details of the structure and
25 function of the invention, the disclosure is illustrative only, and changes may be made in

- 1 detail, especially in matters of shape, size, and arrangement of parts within the
- 2 principles of the invention to the full extent indicated by the broad general meaning of
- 3 the terms in which the appended claims are expressed.